

# Product Specification For IP67 LED T14-L Tube Light

Specially Designed for Mushroom Houses

Beam Angle: 270°

Main Function: Resist Water Jet, High Temperature, and Ammonia gas

# 1. PRODUCT DESCRIPTION

Good lighting is not only necessary for the people working in the terrible environment where mushrooms grow, but also important for the mushrooms. Proper illumination can help mushrooms grow better. In the highly aggressive and extremely damp environment, the lighting needs to be anti-ammonia, and it has to be able to withstand steam and water leaks, high temperature and water jet resistance.

#### **FEATURES**

- · Withstand steam and water leaks
- IP67 waterproof index for high pressure water jet
- High temperature steam and ammonia gas resistant
- Operation temp: -20°C-50°C
- Storage temp: -30°C-95°C
- Steaming temp: 95°C MAX
- High power factor (PF>95)
- Wide input voltage range from 100-265Vac
- Long lifespan time >50,000hrs
- · Certificate CE ROHS
- 3-year warranty



- Mushroom Farms
- Poultry Farms
- Pig Farms

# 2. LIGHTING DETAILS INFORMATION



MODEL NO.	HT-T14AC25W12FE	HT-T14AC30W15FE	HT-T14AC35W18FE
POWER	25W	30W	35W
DIMENSION	L: 1200mm; OD: 36mm	L: 1500mm; OD: 36mm	L: 1800mm; OD: 36mm
LED INFO.	182pcs	208pcs	234pcs

INPUT VOLTAGE	100-264 Vac; 180-264Vac
CRI (RA)	>80
OPERATE TEMP	¦ -20 - 50°C
DIMMABLE	Non Dimmable
STORAGE TEMP	-30 - 90°C
LED TYPE	SMD2835
LUMEN	110 lm/W
CCT	2700-6500K / Blue / Green / Red
LIFESPAN	50000 h
COVER	Milky; Transparent
MATERIAL	PC Cover; Aluminum
BEAM ANGLE	270°
IP GRADE	IP67

# 3. CONNECTION WAY

Double end with cable



Single end with cable



REMARK: The cable length can be customized according to your specifications.


# 4. STRUCTURE IMAGE




Structural IP67 Waterproof:

Resist steam and water leaks, high pressure water jet, and Ammonia;

# 5. INSTALLATION



### 6. BRACKETS TYPES



#### REMARK:

- This unit MUST be installed and wired by a qualified electrical contractor;
- Please cut the power off when install and remove the products to avoid the risk of electric shock;
- · Ensure that the fixed plate should be firmly afforded 2kg;
- Each LED tube should be not less than 2PCS screws or bolts;
- Fixture control gear/AC cable MUST BE MOUNTED ABOVE any insulation covering and waterproof box;
- Do not look directly at the LED light source for a long time.

## 7. PACKING INFORMATION

MODEL NO.	HT-T14AC25W12FE	HT-T14AC30W15FE	HT-T14AC35W18FE
Cable-out Type	Single end with cable		
Power	25W	30W	35W
PCS/CTN	25PCS	25PCS	25PCS
CARTON SIZE	131 x 32 x 32 cm	161 x 32 x 32 cm	191 x 32 x 32 cm
GROSS WEIGHT	28.5KG	32.5KG	34.5KG





# 8.1 PROJECT REFERENCE



Slovakia Turkey Farm



Australia Chicken Farm



Netherlands Pig Farm





Netherlands Mushroom House

# 8.2 PROJECT REFERENCE



Netherlands Mushroom House